

## Sewing Pattern — Skirt 5358

Recommendations on fabric: denim.

You will also need: fusing; eyelets, and cord

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams, 2 cm for hem

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Centre back panel – 2 pieces
2. Back inset 1 – 2 pieces
3. Back inset 2 – 2 pieces
4. Side panel – 4 pieces
5. Centre front panel – 1 piece
6. Front inset 1 – 2 pieces
7. Front inset 2 – 2 pieces
8. Waist facing – 1 piece
9. Guard – 1 piece
10. Closure facing – 2 pieces

Fusing:

closure facing, guard piece, waist facing

### **INSTRUCTIONS:**

1. Apply the fusing to the wrong side of closure facing, guard piece, waist facing.
2. Stitch curved edges of the: side front panel/front inset 2/ front inset 1/ centre front panel. Neaten the seams, press them; make decorative stitches 0.5 cm away from the joining seams.
3. Stitch curved edges of the: side back panel/back inset 2/ back inset 1/ centre back panel. Neaten the seams; press them. Make decorative stitches 0.5 cm away from the joining seams.
4. Stitch the skirt side edges. Neaten and press the side seams.
5. Neaten the back panel centre edges; stitch the seam up to the closure notch. Press the seam open.

6. Fold the guard piece in half lengthways and overstretch its upper/lower edges. Turn it right side out and press.
7. Stitch the side edges of the waist and closure facing. Neaten the facing raw edges.
8. With the facing uppermost overstretch the garment upper edge overstretching the back panel right centre edge. Understitch the seam through the facing and the seam allowance. Trim the right corner seam allowance. Fold the facing to the wrong side; press the upper/centre edging.
9. Neaten the guard side edge. Stitch it under the left back centre edge. Topstitch folded left facing edge to the previously made seam.
10. Stitch and press the hem.
11. Attach the eyelets according to the marks and pull the cord in.

**TECHNICAL DRAWING:**

