

Sewing Pattern — Dress 5357

Recommendations on fabric: denim

You will also need: fusible interfacing, zipper

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams, 2 cm for hem

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Fabric:

1. Back – cut 2
2. Back band/facing – cut 4
3. Side front –cut 2
4. Center front – cut 2
5. Front band/facing – cut 2

Interfacing: 2 back facing, 1 front facing

INSTRUCTIONS:

1. Apply the interfacing to the facing wrong sides.
2. Sew the front and back darts. Press toward center.
3. Sew side front to center front, serge and press seams toward center. Sew center front seam. Serge and press toward right.
4. Sew side seams. Serge and press toward back.
5. Sew side seams of the bands and side seams of the facings, press open. Sew the upper edge of the band to facing, right sides together. Clip into curves. Turn and press. Serge facing inner edge.
6. Pin the band to the neckline, right sides together, and sew. Clip into curves. Press facing onto wrong side.
7. Serge center edges of backs separately. Sew center back seam from zipper end mark to hem. Press seam apart, including opening for zipper. Sew in zipper. Slipstitch the ends of the facing to the zipper tape. Topstitch the top edge of garment.
8. Serge the bottom edge of garment. Fold and press onto wrong side and topstitch.

TECHNICAL DRAWING: