

Sewing Pattern — Jacket with flounce 5353

Recommendations on fabric: denim

You will also need: fusing; 1 button

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowances: 1 cm for all seams, 3 cm for sleeve hems

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Centre back – 2 pieces
2. Side back – 2 pieces
3. Side front – 2 pieces
4. Back neck facing – 1 piece
5. Centre front – 2 pieces
6. Under collar – 1 piece
7. Top collar – 1 piece
8. Front facing – 2 pieces
9. Flounce – 2 pieces
10. Upper sleeve – 2 pieces
11. Lower sleeve – 2 pieces

Fusing: front/back facing, under collar piece.

INSTRUCTIONS:

1. Apply the fusing to the wrong side of the front/back facing, under collar piece.
2. Make up and shape the collar.
3. Stitch the back/front curved edges; neaten the seams. Press the front seams towards the centre front, press the back seams backwards.

4. Neaten the front facing raw edges. Neaten the back facing raw edge.
5. With right sides together, pin the front facing to the garment along the front edges. Stitch the facing. Trim the seam allowances. Trim the seam allowances diagonally across the front corners. Press the seam allowances away from the garment. Understitch next to the seam along the closure segment; through the front piece and the seam allowance at the lapels. Turn the facing to the wrong side, and press.
6. Stitch and neaten the back centre seam. Press the seam.
7. Stitch the shoulder/side seams; neaten them. Press these seams backwards.
8. Join the front and back neck facing across the shoulder seams; press the seams open.
9. Neaten sleeve elbow seams. Stitch them and press open.
10. Stitch the sleeve front seams. Neaten them. Press the seams towards the front. Press the sleeve hems.
11. Stitch the sleeves to the armholes matching the notches; neaten the seams.
12. Stitch the collar to the neckline.
13. Stitch the flounce centre edges; neaten the seam. Press the seam to the right. Stitch the flounce to the garment lower edge; neaten the joining seam. Fold the front facing lower edges to the wrong side and sew them to the previously made seam.
14. Make buttonhole in the front right piece, sew button on the left piece.

TECHNICAL DRAWING:

