

## Sewing Pattern — Skirt 5352

Recommendations on fabric: denim

You will also need: fusing, zipper

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Main fabric:

1. Back panel – 1 piece
2. Front narrow gusset – 1 piece
3. Side right front panel – 1 piece
4. Front gusset – 1 piece
5. Side left front panel – 1 piece
6. Front lower inset – 1 piece
7. Diagonal lower panel – 1 piece
8. Lower back gusset – 1 piece
9. Front facing – 1 piece
10. Back facing – 1 piece

Fusing: front/back facing

### **INSTRUCTIONS:**

1. Apply the interfacing to the wrong side of the front/back facings.
2. Stitch the front narrow gusset to the side right front piece. Neaten and press the seam.
3. Stitch the front gusset to the front narrow gusset. Neaten and press the seam.
4. Stitch the front lower inset to the side left front. Neaten the seam; press it.
5. Stitch the diagonal lower piece to the back panel. Neaten the seam; press it.
6. Stitch the back lower gusset to the diagonal lower piece. Neaten the seam and press it.

7. Neaten and stitch the side edges up to zipper notch. Press the seams open. Sew the zipper in.
8. Neaten the hem and the front asymmetrical edge. Stitch the front edges up to the notches; press the seam open.
9. Stitch the front/back facing side seams; press them open.
10. With right sides together, stitch the facing to the garment along the top edges. Topstitch the seam allowance to the facing 0.2 cm above the seam. Turn the facing under and press the garment edging. Slipstitch the ends of the facing to the zip tape.
11. Press the hem/front asymmetrical edge under. Topstitch them to the garment.

**TECHNICAL DRAWING:**

