

Sewing Pattern — Skirt 5351

Recommendations on fabric: denim

You will also need: fusible interfacing, button, zipper

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Fabric:

1. Front right panel – cut 1
2. Front left panel – cut 1
3. Back panel –cut 2
4. Front left yoke – cut 2
5. Front right yoke – cut 2
6. Back yoke –cut 2
7. Pocket bag – cut 2
8. Pocket welt – cut 2
9. Flounce – cut 2

Fusible interfacing: inner back/front yokes

INSTRUCTIONS:

1. Apply the interfacing to the wrong side of the inner back/front yokes.
2. Mark and press pleats at the front/back panels. Topstitch the pleats.

3. Sew center back seam, Neaten seam and press toward the right; make a decorative stitch or topstitch 0.2 cm away from the seam through the seam allowance.
4. Sew the top yoke pieces to the front panels. Neaten the seams; press them upwards. Neaten the side edges.
5. Mark the pocket positions on the front. Fold and press the welt in half lengthways; topstitch the welt to the wrong side of the pocket bag placing the welt wrong side inside; topstitch this piece to the garment according to the marks. Cut the pocket entrance making diagonal slits 1-1.5 cm toward the corners. Pull the pocket bags inside leaving the pocket welt on the right garment side. Tack and press the seams around the pocket entrance. Sew the welt side seam allowances and the pocket entrance corners together working on the wrong side of garment. Sew the pocket bags; neaten the seam. Topstitch the pocket to the garment around the pocket side/lower edges with double decorative stitch.
6. Serge the flounce lower edges and press it under. Topstitch 0.5 cm from the fold-line.
7. Sew the flounce to the front panels. Neaten/serge the joining seams; press them.
8. Press the right front center seam allowance under; topstitch this edge to the other front piece according to the marks. Sew the zipper in and make a decorative stitch on the right piece.
9. Sew the side seams; neaten and press toward back.
10. Sew the side edges of the inner yokes; press the seams open. Neaten/serge the inner yoke lower edge. Pin the top/inner yokes face to face and sew them together along the upper edge. Topstitch the seam allowance to the inner piece. Press the edging. Topstitch the inner yoke lower edge through the top yoke above the previously made seam. Slip-stitch the facing center edges to the zip tape.
11. Serge the lower edge of garment; press it under; topstitch the hem to the garment 0.5 cm above the fold-line.
12. Make buttonhole in the right front panel; sew the button on the left front panel.

TECHNICAL DRAWING:

