

Sewing Pattern — Jacket 5349

Recommendations on fabric: denim and a knitted material

You will also need: fusing; 7 buttons; drawstring for the hood

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance : 1 cm for all seams, 3 cm for hem

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back Yoke – 1 piece
2. Back neck facing – 1 piece
3. Side front – 2 pieces
4. Front Yoke – 2 pieces
5. Middle front – 2 pieces
6. Centre front – 2 pieces
7. Front facing – 2 pieces
8. Flap – 4 pieces

Knitted material:

1. Back – 1 piece
2. Sleeve – 2 pieces
3. Centre hood – 1 piece
4. Hood – 2 pieces
5. Cuff – 2 pieces

Fusing: facings

INSTRUCTIONS:

1. Apply fusing to the wrong side of the facings.
2. Stitch the curved edges of the side/middle front. Neaten and press these seams towards the center. Stitch the curved edges of the centre/middle front. Neaten and press them towards the center. Make double decorative stitch 0.2cm away from the seamlines.

3. Stitch the back yoke to the back piece. Neaten this seam and topstitch 0.2cm above the seamline.
4. Stitch the flap pieces together right sides inside. Trim the seam allowances on the corners and turn the flaps inside out. Edgestitch them 0.5cm in.
5. Place the flap to the front yoke lower edge and stitch according to the marks. Stitch the yoke to the front piece. Neaten this seam and topstitch to the yoke with double decorative stitch 0.2 cm above.
6. Neaten the outer edge of the front/neck facing. Stitch the front facings to the front pieces. Turn the edging inside out and edgestitch with double decorative stitch 0.2cm in from the edges. Joining the front/back facings across the shoulder seams.
7. Stitch the side/shoulder seams. Neaten and press them backward.
8. Stitch and neaten the hood pieces. Neaten the front raw edge of the hood, mark and make buttonholes. Fold this edge inside and topstitch. Stitch the hood to the neckline. Overstitch the neckline with the facing. Fix the outer edges of the front facings to the shoulder seams.
9. Stitch the side edges of the cuffs. Stitch and neaten the sleeve seams. Fold the cuffs along the length and stitch to the sleeve lower edges.
10. Stitch the sleeves to the garment according to the notches.
11. Make buttonholes in the right front piece; sew buttons on the left piece. Pull the drawstring into the hood through the buttonholes.

TECHNICAL DRAWING:

