

## Sewing Pattern — Skirt 5347

Recommendations on fabric: denim, bottom-weight skirt fabric  
You will also need: fusible interfacing; zipper

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance : 1 cm for all seams, 2 cm for hem

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.



### **CUTTING:**

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

#### Fabric:

1. Back yoke – cut 2
2. Front yoke – cut 1
3. Back facing – cut 2
4. Front facing – cut 1
5. Skirt Panel – cut 2

Fusible interfacing: back/front facing

### **INSTRUCTIONS:**

1. Apply interfacing to the wrong side of back/front facing.
2. Mark and sew the back yoke darts. Press toward center.
3. Serge the yoke side edges; sew yoke side seam. Press seams open.
4. Serge center front edges separately. Sew center front seam and press open. Make pleats according to the notches on front-back panel; press and baste to top edge. Sew yoke to the front-back panel. Serge and press seam toward yoke.

5. Sew the facing side seams and press the seams open. Serge facing lower edge and center back edge.
6. Serge center back panel edges separately. Sew center back seam from zipper mark to lower edge of garment. Press seam open, including opening for zipper. Sew in zipper.
7. With right sides together, sew the facing to the garment along the top edge. Understitch the seam allowance to the facing 0.2 cm above this seam. Turn the facing to the wrong side of skirt and press. Fold and slip-stitch the ends of the facing to the zipper tape.
8. Serge lower edge of garment. Turn and press onto wrong side, and topstitch.

**TECHNICAL DRAWING:**

