

Sewing Pattern — Skirt 5341

Recommendations on fabric: artificial suede

You will also need: fusing, blind zipper

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: 1 cm. for all seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Upper left back panel – 1 piece
2. Upper right back panel– 1 piece
3. Upper centre back panel – 1 piece
4. Middle right back panel – 1 piece
5. Middle Back panel – 1 piece
6. Lower back panel – 1 piece
7. Lower right front panel – 1 piece
8. Side gusset of the right front panel– 1 piece
9. Centre gusset of the right front panel– 1 piece
10. Upper right front panel – 1 piece
11. Middle right front panel – 1 piece
12. Upper left front panel– 1 piece
13. Middle left front panel – 1 piece
14. Lower left front panel – 1 piece
15. Waistband – 1 piece

INSTRUCTIONS:

1. Stitch side seam of the front and centre front gussets. Press the seam open. Make a decorative stitch 0.2 cm away from the joining seam.
2. Stitch the lower right front panel to the stitched gussets; press the seam open. Make a decorative stitch 0.2 cm away from the joining seam.
3. Stitch the middle right panel to the middle front panel; press the seam open. Make a decorative stitch 0.2 cm away from the joining seam.
4. Stitch the upper front panel to the middle front panel; press the seam open. Make a decorative stitch 0.2 cm away from joining seam.
5. Stitch the middle left front panel to the lower left front panel; press the seam open. Make a decorative stitch 0.2 away cm from the joining seam.
6. Stitch the upper right front panel; press the seam open. Make a decorative stitch 0.2 cm away from the joining seam.
7. Stitch the middle back panel to the lower back panel; press the seam open. Make a decorative stitch 0.2 away cm from the joining seam.
8. Stitch the middle right back panel to the middle panel; press the seam open. Make a decorative stitch 0.2 away cm from the joining seam.
9. Stitch side edges of the upper centre back panel and the upper left back panel. Press the seam open. Make a decorative stitch 0.2 away cm from the joining seam.
10. Stitch side edges of the upper centre back panel and the upper right back panel; press the seam open.
11. Stitch the stitched upper back panel to the middle back panel. Make a decorative stitch 0.2 cm away from the joining seam.
12. Stitch the skirt side seams.
13. Fold the waistband in half lengthways and press it along the center. Stitch the side ends. Turn the waistband right side out and press it. Stitch one long edge of the waistband to the garment according to the waistband notches and the side seams inserting carriers. Topstitch the waistband other long edge on the joining seam.
14. Make buttonholes and sew buttons.

TECHNICAL DRAWING:

