

Sewing Pattern — Jacket 4210

Recommendations on fabric: natural or mixed thin costume fabrics.

You will also need: fusing; lining; 4 hooks with eyes; 6 buttons; shoulder pads, sleeve heads.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: all seams - 1 cm, on jacket hem and hem of sleeve - 4 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Central back part – 2 details
2. Side back part – 2 details
3. Central front part – 2 details
4. Side upper front part – 2 details
5. Upper sleeve part – 2 details
6. Lower sleeve part – 2 details
7. Back neckline facing – 1 detail
8. Front stand – 4 details
9. Buttonstand – 2 details
10. Upper collar – 1 detail
11. Lower collar – 1 detail
12. Flap – 4 details
13. Bospal (Frame) – 4 details
14. Front part yoke – 2 details

Lining:

1. Central back part – 2 details
2. Side back part – 2 details
3. Side front part – 2 details
4. Upper sleeve part – 2 details
5. Lower sleeve part – 2 details
6. Bigger pocket bag – 2 details
7. Smaller pocket bag – 2 details

Fusing: central front part, buttonstand, back part neckline facing, hem of sleeve, flap, bospal, upper collar

INSTRUCTIONS:

1. Apply fusing to details. Apply fusing to back part neckline and pocket opening on central details of front part.
2. Sew relief edges on back part. Press the seam apart. Sew middle edge of back part. Press seam allowance apart.
3. Stitch yoke to front part. Press apart the seam towards center. Sew relief edges on front part. Press apart the seam towards center.
4. Fold flaps right sides together, overstitch, cut on folds and turn onto right side. Fold frames in half lengthwise right sides together and press. Stitch lower frame to central front part seam allowance. Stitch upper bospal with the flap to lower edge of side part. Finish cutting pocket opening on central part. Turn facings and flap onto right side and press. Stitch bigger pocket bag to seam allowance of upper bospal, smaller pocket bag – to lower bospal. Sew pocket bags. Fix corner with double stitch.
5. Sew and press apart side and shoulder edges of the jacket.
6. Fold top collar with lower and overstitch on ends and outer edge. Start and finish the stitch exactly near marked line of collar connecting seam. Slash seam allowances in corners, slash near marker. Turn collar out, straighten and press.
7. Fold details of decorative front stand right sides together and overstitch on lower and outer edge up to the notch, determining the end of collar connection. Slash seam allowances in corners. Turn front stands out, straighten and press. Sew collars into decorative stands on gorge edges. Press apart the seam.
8. Sew and press apart shoulder edges of back part neckline facing buttonstand.
9. Put buttonstand onto front part right side right side downwards, insert decorative front stands and collar between them. Fix with pins and overstitch along stand part and neckline.
10. Sew and press apart sleeve elbow seam and vent corners on lower and upper parts of sleeve. Press sleeve elbow seam apart, make a notch and press the vent. Put a cross fixing stitch along sleeve vent. Press hem of sleeve. Sew and press apart front sleeve seam. Sew sleeves into armholes according to notches, easing in rounded part. Sew in shoulder pads, sew sleeve heads.
11. Sew seams on lining details and sew in sleeves, leaving a slit in front right seam of sleeve. Stitch lining to buttonstands and facing.
12. Press hem of the jacket. Stitch lining to jacket hem. Turn jacket through the slit in sleeve. Sew slit in sleeve.
13. Sew hooks on right front part, sew eyelets on left front part.
14. Sew buttons on the vent.

TECHNICAL DRAWING:

