

Sewing Pattern — Jacket 5338

Recommendations on fabric: wool or semi-wool fabric

You will also need: fusing, decorative buckle, 2 medium size buttons; sleeve heads, lining fabric

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: 1 cm. for all seams, 3 cm. for hems.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Centre back – 2 pieces
2. Side back – 2 pieces
3. Side front – 2 pieces
4. Centre front - 2 pieces
5. Front facing– 2 pieces
6. Belt – 1 piece
7. Upper sleeve – 2 pieces
8. Lower sleeve – 2 pieces

Lining:

1. Centre back – 2 pieces
2. Side back – 2 pieces
3. Side front – 2 pieces
4. Centre front without the front facing width - 2 pieces
5. Upper sleeve – 2 pieces
6. Lower sleeve – 2 pieces

Fusing: front facings, belt.

INSTRUCTIONS:

1. Iron the interfacing to the wrong side of the front facings and the belt.

2. With right side inside, fold the belt in half lengthways, and stitch leaving one short end open. Turn the belt right side out through the open edge and press it flat. Fix buckle to the belt.
3. Stitch the centre back edges. Stitch the front/back curved edges.
4. Overstitch with the front facing the centre front edges, integrated belt, neckline, upper edge of the integrated collar. Stitch the front facing lower edges to the front strictly along the marked hemline. Trim the seam allowances on the corners. Trim the seam allowances on the belt corners. Trim and notch the seam allowance on the curves. Turn the jacket right side out and press.
5. Stitch the side edges inserting the belt into the left seam according to the marks. Stitch the shoulder seams and notch the seam allowances in the corners. Press the seams open.
6. Stitch pieces of the collar together. Press the seam open. Stitch the top collar piece to the neckline.
7. Stitch sleeve edges. Press the seams open.
8. Place the sleeves inside the jacket (face-to-face) so that the sleeve's notches match with armhole notches and stitch. Fix sleeve heads to the garment.
9. Stitch lining pieces, leaving a slit in front seam of the right sleeve and press the seams. Stitch the lining to the raw edges of the front facing and to the top collar. Press the neckline seams open and fix the allowances together. Stitch the lining sleeve hems to the jacket sleeve hems, stitch the lining hem to the hem of the jacket. Turn the jacket right side out through the sleeve slit. Stitch the slit.
10. Make 2 buttonholes in the right end of the belt. Attach the buttons to the left side seam according to the buttonholes.

TECHNICAL DRAWING:

