

Sewing Pattern — Dress 5335

Recommendations on fabric: stamped satin

You will also need: lining; zipper

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams, 2 cm for hem.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Centre back – 2 pieces
- 2 Side back – 2 pieces
3. Side front– 2 pieces
- 4 Centre front – 1 piece
5. Skirt back panel – 2 pieces
6. Skirt front panel – 1 piece

Lining:

1. Center back – 2 pieces
2. Side back – 2 pieces
3. Side front– 2 pieces
4. Centre front – 1 piece

INSTRUCTIONS:

1. Stitch front/back curve edges and neaten these. Press the front seams towards the centre front, press the back seams backwards.
2. Stitch the bodice shoulder/side seams, neaten them. Press the seams backwards.
3. Stitch lining pieces. Press the shoulder/side seams backwards.
4. Overstitch edges of neckline and armholes with the lining.

5. Stitch the skirt side seams; neaten them. Press the seams backwards.
6. Stitch the skirt to the bodice. Neaten the joining seam.
7. Neaten the centre back edges. Stitch back centre seam up to the closure notch. Press it open pressing the closure slit. Sew the zipper in.
8. Fold the hem to the wrong side and stitch in place.

TECHNICAL DRAWING:

