

## Sewing Pattern — Top 5333

Recommendations on fabric: taffeta or brocade

You will also need: 1 zipper; lining

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



### **CUTTING:**

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

#### **Main fabric:**

1. Center back – cut 2
2. Side back – cut 2
3. Side front – cut 2
4. Center front – cut 1

#### **Lining:**

1. Center back – cut 2
2. Side back – cut 2
3. Side front – cut 2
4. Center front – cut 1

## **INSTRUCTIONS:**

1. Sew side fronts to center front, and side backs to center backs. Serge and press seams toward center.
2. Sew side/shoulder seams. Serge and press toward back.
3. Sew lining same as fabric.
4. With right sides together sew the lining to the garment neck edge, and armholes using the two-step method. Here is a tutorial on this method: [Two-Step Method](#). Sew lower edge of lining and garment, right sides together. Turn and press.
5. Baste lining and garment together at back center seam. Serge the back center edges separately. Sew the center back seam from the zipper mark to hem. Press seam apart including opening for zipper. Sew in zipper.

## **TECHNICAL DRAWING:**

