

Sewing Pattern — Blouse 5330

Recommendations on fabric: jersey

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance : 1 cm. for all seams, 2 cm. for garment/sleeve hem

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back – 1 piece
2. Front – 1 piece
3. Right sleeve front – 1 piece
4. Right sleeve back – 1 piece
5. Left sleeve – 1 piece
6. Left sleeve coulisse – 1 piece

ADVICE: to prevent seam from stiffing, sew details with special (zig zag) stitch. To prevent hem from stiffing neaten it with overlock and then stitch using double needle. Do the same for all edges must stay elastic.

The above is not for industrial manufacturing.

INSTRUCTIONS:

1. Neaten the central edges of the right sleeve. Stitch them leaving a slit according to the notches. Press the seam open. Topstitch the seam allowances 0.7 cm away from the joining seam leaving a slit close to the lower notch for pulling tie in; stop stitching 2 cm before the end.
2. Pin the coulisse stripe to the sleeve wrong side according to the marks. Unfold the stripe lower end. Topstitch the stripe along the marking.
3. Make the ties.

4. Stitch the shoulder/side seams and neaten them. Press these seams backwards.
5. Stitch the sleeve inner seams and neaten them. Press the seams backward.
6. Stitch the sleeves to the armholes according to the notches.
7. Neaten the front/back neck edges, garment hem and sleeve hems. Fold the neaten edges to the wrong side and topstitch them. Insert the ties into the coulisses. Pull the ties ends gathering the fabric.

TECHNICAL DRAWING:

