

Sewing Pattern — Dress 4209

Recommendations on fabric: fabric suitable for dresses.

You will also need: lining; blind zipper; fusing; thin decorative belt.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: all seams 1 cm, lower edge of lower part of the back – 2.0 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Central back part – 2 details
2. Side back part – 2 details
3. Lower back part - 2 details
4. Right lower front part– 1 detail
5. Left lower front part– 1 detail
6. Side front part - 2 details
7. Central front part - 1 detail
8. Front part yoke - 2 details
9. Facing of right part - 1 detail
10. Facing of left part - 1 detail
11. Sleeve - 2 details
12. Belt loop — 1 detail
13. Back neckline facing – 2 details
14. Front neckline facing – 2 details

Lining:

1. Sleeve - 2 details

Fusing:

1. Back neckline facing – 2 details
2. Front neckline facing – 2 details
3. Facing of right part - 1 detail
4. Facing of left part - 1 detail

INSTRUCTIONS:

1. Apply fusing to details of the hem and neckline facings, as well as to one-piece facing of central part of the front.
2. Sew princess seams on back part, press seam allowances towards center and serge.
3. Sew darts on lower parts of the back, press depths towards center. Sew top and lower parts of the back, press seam allowances upwards and serge. Serge center edge of the back separately on each detail. Sew center edge from marker up to hem. Press the seam apart, pressing the slit for zipper. Sew in the zipper.
4. Serge one-piece facing of central part of the front. Sew princess edges of front part from fold downwards, press seam allowances towards center and serge. Stitch yokes to front part, press seam onto yoke and serge.
5. Make and fasten pleats on right lower part of the front. Fold right lower part of the front with facing right sides together and overstretch outer edge. Slash seam allowances on rounded parts, turn the facing onto wrong side, press. Fold left lower part of the front with facing right sides together and overstretch outer edge. Slash seam allowances on rounded parts, turn the facing onto wrong side, press. Stitch left lower part of the front to right part's facing, press and serge seam allowances, serging inner edge of right part's facing at the same time.
6. Sew upper and lower front parts, press seam allowances upwards and serge.
7. Sew shoulder seams, press seam onto back part and serge. Serge lower edge of the back. Sew side seams, enveloping front part with back part allowance. Press seam allowances towards back part, serge. Turn lower seam allowance onto back part, press and undersew with invisible stitches.
8. Sew shoulder seams of the neckline facings, press seam allowances apart. Serge outer edge. Fold the facing with neckline right sides together. Leaving 5 mm to zipper edges, turn the facing away and pin to top edge of the dress. Turn seam allowances along zipper onto right side of the dress and pin to neckline edge on top of the facing. Overstretch back part neckline edge, front part neckline edge and front part edge up to marker. Slash seam allowances on rounded parts, slash away in corners. Sew together the edge of one-piece facing of front's central part and the edge of front part neckline facing, from marker downwards. Turn detail onto right side and press. Turn in the center edge of the facing and tack to zipper tape.
9. Sew edge of sleeve, press seam allowances and serge. Sew edge of sleeve from lining. Fold lining with the sleeve right sides together and overstretch lower edge. Slash seam allowances, turn the sleeve onto right side, press. Fix the sleeve with lining along rounded part and then sew as one detail.
10. Sew sleeve into the armhole, aligning notches, press and serge seam allowances.
11. Serge one long edge of the belt loop. Fold belt loop in three layers and topstitch on long sides. Cut belt loop into 2 details. Sew belt loops at waist line on side seams. **ADVICE:** Wear the dress with the belt.

TECHNICAL DRAWING:

