

Sewing Pattern — Trousers 5326

Recommendations on fabric: silk velvet or satin (for stripes), silk (as a garment fabric)

You will also need: fusing, 1 zipper of 20 cm length

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance : on hem – 3cm, all other seams - 1 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Stripe – 2 pieces
2. Front – 2 pieces
3. Back – 2 pieces
4. Front facing – 1 piece
5. Back facing – 2 pieces

Fusing: facings

INSTRUCTIONS:

1. Apply the interfacing to the wrong side of facings.
2. Stitch front/back darts, press them towards the center.
3. Stitch stripes to the front side edges. Neaten the joining seams and press them toward the front. Stitch the side stripes to the back. Neaten the seams. Press them backwards. Neaten the hems. Stitch inside leg seams and press them open. Stitch the crotch seam up to the zipper notch. Make another stitch along the previously made.
4. Press the slit allowances to the wrong side. Stitch the zipper in with its teeth hidden.
5. Sew the front and back facing's side edges. Neaten the facing lower edge. Lay the facing on the garment right sides together; overstretch garment top edge with the facing. Topstitch the seam

allowance to the facing 0.2 cm away from the joining seam. Fold the facing central raw edges under and sew to the zip.

6. Press the hems to the wrong side and topstitch them.

TECHNICAL DRAWING:

