

Sewing Pattern —Skirt 5323

Recommendations on fabric: artificial leather or suede

You will also need: fusing; 1 zipper

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance : on hem – 3cm, all other seams - 1 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Side gusset – 4 pieces
2. Upper side panel – 4 pieces
3. Lower side panel – 4 pieces
4. Centre inset – 4 pieces
5. Centre gusset – 4 pieces
6. Front yoke – 2 pieces
7. Back yoke – 2 pieces
8. Front facing – 1 piece
9. Back facing – 1 piece

Fusing: front and back facings.

INSTRUCTIONS:

1. Apply fusing to the wrong side of the facings. Stitch darts at the back yoke and press them towards the centre.
2. Stitch the side gusset and the upper side edges. Topstitch the joining seam to the side gusset.
3. Stitch the stitched pieces to the yoke. Topstitch the seam to the yoke.

4. Stitch the centre inset and the centre gusset. Press the seam and topstitch it to the centre inset.
5. Stitch the lower side panel to the central inset. Press the seams and topstitch them to the side panels.
6. Stitch the upper/lower panels. Press the seams upwards and topstitch them.
7. Stitch the right and left pieces of the front/back panels. Press the seams open.
8. Stitch the side seams. With its teeth hidden, stitch the zipper in.
9. Stitch the right edges of the facings. Neaten the raw edge. Pin the facing and the garment. With the facing uppermost, stitch the facing to the garment. Turn the facing to the wrong side of the garment. Topstitch the seam allowance to the facing. Slipstitch the ends of the facing to the zip tap
10. Neaten and topstitch the garment hem.

TECHNICAL DRAWING:

