

Sewing Pattern — Cloak 5316

Recommendations on fabric: artificial leather of two colours

You will also need: fusing; separable zipper; lining

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance : 1 cm for all seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back yoke – 2 details
2. Middle back part – 2 details
3. Lower back part – 2 details
4. Back contrast insert – 2 details
5. Side lower back part – 2 details
6. Side upper back part – 2 details
7. Front yoke – 2 details
8. Middle front part – 2 details
9. Upper front part – 2 details
10. Upper side front part – 2 details
11. Lower side front part – 2 details
12. Front contrast insert – 2 details
13. Stand-up collar – 2 details
14. Front band – 2 details
15. Sleeve – 2 details
16. Sleeve back insert – 2 details
17. Sleeve front insert – 2 details

OUR ADVICE: if wished, you can cut contrast back and front inserts into additional segments, depending on the material length

Fusing: front band, stand –up collar, back yoke, front yoke; hem allowances: sleeve, front contrast insert, back contrast insert.

INSTRUCTIONS:

1. Strengthen the front band, stand-up collar, front yoke, back yoke, sleeve hem, front contrast insert hem, back contrast insert hem.
2. Overstitch inner collar with outer one (right sides together) on the collar fall side.
3. Sew front yoke to front contrast insert. Make decorative stitch on 0.2 cm from front yoke joining seam.
4. Sew middle front part to front contrast insert. Make decorative stitch on 0.2 cm from middle front part joining seam.
5. Sew lower front part to front contrast insert. Make decorative stitch on 0.2 cm from lower front part joining seam.
6. Sew upper side front part to front contrast insert. Make decorative stitch on 0.2 cm from upper side front part joining seam.
7. Sew lower side part to contrast front insert. Make decorative stitch on 0.2 cm from lower side front part joining seam.
8. Sew back yoke to back contrast insert. Make decorative stitch on 0.2 cm from back yoke joining seam.
9. Sew upper side part to back contrast insert. Make decorative stitch on 0.2 cm from upper side back part joining seam.
10. Sew middle back part to back contrast insert. Make decorative stitch on 0.2 cm from back yoke joining seam.
11. Sew lower back part to back contrast insert. Make decorative stitch on 0.2 cm from lower side back part joining seam.
12. Sew lower side back part to back contrast insert. Make decorative stitch on 0.2 cm from lower side back part joining seam
13. Sew shoulder and side seams.
14. Sew inner stand-up collar to the neckline.
15. Fold front parts right sides together coinciding yokes, then measure front edge lengths. Sew the zipper to edges. Fold edges at zipper area under and press through pressing cloth.
16. Sew outer stand-up collar to the front band.
17. Fold front band and front part right sides together. Overstitch ends of stand-up and front band, from the front part side. Sew lower edges of front bands to front part strictly along the marked line of hem turning-under. Cut front edge upper and lower corners Turn edges into right side, trim seams. Make decorative stitch on 0.5 cm from the edge.
18. Sew sleeve back insert to the sleeve. Make decorative stitch on 0.2 cm from back sleeve insert

joining seam

19. Sew sleeve front insert to the sleeve. Make decorative stitch on 0.2 cm from sleeve front insert joining seam

20. Sew sleeve edges. Sew sleeves into armholes according to notches.

21. Sew shoulder pads and sleeve heads into.

22. Sew seams into lining, then sew sleeves into, with a hole in the sleeve front seam. Sew sleeves into and press the lining.

23. Sew lining to front bands and outer stand-up inner edges. Press joining seam allowances apart, then sew near seam. Sew lining sleeves and garment hems to fabric ones.

TECHNICAL DRAWING:

