

Sewing Pattern — Jacket 5312

Recommendations on fabric: velvet with stretch

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance : 1 cm for all seams

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Fabric:

1. Back yoke – cut 1
2. Center back – cut 1
3. Side back - cut 2
4. Lower back band - cut 2 (1 is facing)
5. Front yoke – cut 2
6. Side front – cut 2
7. Middle front – cut 2
8. Center front – cut 2
9. Button band/collar – cut 4 (2 are facings)
10. Sleeve – cut 2
11. Cuff – cut 2
12. Flap – cut 4
13. Upper pocket bag –cut 4

Fusible interfacing: outer front bands, cuffs, 2 outer flaps

INSTRUCTIONS:

1. Apply interfacing to listed pieces.
2. Sew side front to middle front. Sew middle front to center front. Make a decorative double stitch 0.2 cm from joining seam.
3. Pin flaps right sides together, then sew along the outer edges. Trim corners and turn right side out. Make a decorative double stitch along flap outer edge 0.2 cm from the edge. Match flap open edges and yoke edges (flap on front yoke right side), pin upper pocket bag on the flap, then tack. Match lower part of the bag and lower front right side. Sew flap and the bag. Sew the yoke to the front. Turn the bag inside, straighten and topstitch. Tack the bag along the outer edge and topstitch the bag on the front. Snip the seam near the pocket. Press the joining seam toward the yoke, then topstitch.
4. Sew side back to center back. Sew back yoke to back. Make a decorative double stitch 0.2 cm from joining seam.
5. Sew shoulder and side seams. Press toward back and topstitch.
6. Sew collar center seam on button band/collar. Sew side seam of button bands/collar to lower back. Repeat for facing. Pin entire band facing to edge of garment, right sides together, and sew. Pin band facing, right sides together, to button/collar band and sew outer edge. Clip into curves, undersew, turn and press. Turn inner seam allowance of facing under, and sew to joining seam. Make a double decorative stitch along the edge and the collar 0.2 cm from the edge. Topstitch one-piece outer collar and band 0.2 cm from the seam.
7. Sew sleeve seams. Make a gathering stitch along sleeve cap for ease. Sew sleeves to armholes, matching seams and adjusting ease. Press lower cuff upper edge under 1 cm. Fold the cuff along the center, and sew side edges. Trim corners and turn the cuff right side out.
8. Sew upper cuff to sleeve lower edge, then topstitch the lower cuff into joining seam.
9. Make buttonholes on the flap and the cuff, then sew buttons. Make buttonholes on right front and sew button on left.

TECHNICAL DRAWING:

