

Sewing Pattern — Safari jacket 5304

Recommendations on fabric: silk and viscose

You will also need: clue interfacing; 9 buttons

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front part - 2 details
2. Back part - 1 detail
3. Front band - 2 details
4. Sleeve - 2 details
5. Collar - 2 details
6. Upper patch pocket – 2 details
7. Lower patch pocket – 2 details
8. Upper patch pocket flap – 4 details
9. Lower patch pocket flap – 4 details
10. Epaulettes – 4 details
11. Cuff – 4 details
12. Belt – 2 details
13. Band loops – 3 details

Clue interfacing: front band, outer collar, cuffs, flaps.

INSTRUCTIONS:

1. Strengthen the front band, outer collar, cuffs and flaps with clue interfacing.
2. Press box pleats into pockets. Box pleats are the wrong side of inverted box pleat.
3. Fold under and topstitch pocket one-piece facings, then press side and lower allowances of pockets (according to patterns).
4. Topstitch pockets on the front part coinciding them to marking.
5. Overstitch upper and lower pockets flaps. Make decorative stitch on 0.3 cm from the edge. Tack flap upper edge and sew in accordance with marking. Turn flaps out and topstitch on the front part.
6. Tack front band inner edges. Overstitch front part with front bands.
7. Sew shoulder seams.
8. Sew side seams.
9. Overstitch inner collar with outer one, then turn out and press.
10. Turn front bands into wrong side. Oversew and press edges. Sew inner collar to the neckline, fold the outer collar open edge under and topstitch along the inner collar joining seam. Sew front band into shoulder seams with 1 cm width stitch.
11. Sew sleeve seams.
12. Press lower cuff upper edge on 1 cm. Overstitch lower cuff with upper one and turn in out into right side.
13. Sew upper cuff to sleeve hem. Topstitch lower cuff.
14. Overstitch epaulettes, turn them out, then press and make decorative stitch on 0.3 cm from the edge.
15. Sew sleeves into armholes, inserting epaulettes and fitting along caps.
16. Sew both belts. Fold the belt along the center and overstitch it along three sides, with unstitched place in the middle. Turn the belt into right side, press and sew the place.
17. Fold the belt loop along the center right sides together, equalize edges and overstitch on 0.5-0.7 cm from edges. Then turn it into right side, place the seam along the center bend, or make an edging into wrong side on 0.1-0.2 cm, then press.
18. Topstitch belt loops according to marking on side seams and on back enter. Pull the belt into loops.
19. Tack hem allowance, turn into wrong side and topstitch along the edge.

20. Tack button holes into epaulettes and flaps.

21. Work a button holes into right front part and sew buttons to left one.

TECHNICAL DRAWING:

