

## Sewing Pattern — Leather jacket 5303

Recommendations on fabric: artificial and natural leather, suede, suit nature or combine fabric.

You will also need: clue interfacing; metal separable zipper

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Front part - 2 details
2. Front part side – 2 details
3. Back part - 1 detail
4. Back part side – 2 details
5. Front band - 2 details
6. Sleeve - 2 details

Lining:

1. Front part - 2 detail
2. Front part side – 2 details
3. Back part - 1 detail
4. Back part side – 2 details
5. Sleeve - 2 details

Clue interfacing: front band.

### **INSTRUCTIONS:**

1. Strengthen the front band, preferably to strengthen upper back part, lower sleeve, lower front/back parts.
2. Sew lining seams.
3. Sew lining front parts to front bands.
4. Sew darts into front part.
5. Sew relieves into front part.
6. Sew the zipper to front parts.
7. Sew relieves into back part.
8. Sew shoulder seams.
9. Sew side seams.
10. Overstitch front part edges with font bands. Overstitch back neckline with facing.
11. Sew sleeve seams.
12. Sew sleeves into, fitting along caps.
13. Sew the lining to jacket hem allowance. Sew sleeve lining to fabric sleeve hem. Fix it by hand under the armhole and along the jacket hem. Turn the lining and the jacket right side out. Sew fabrication hole in the sleeve.
14. Topstitch garment and sleeve hems along the edges.

### **TECHNICAL DRAWING:**

