

Sewing Pattern — Top 5296

Recommendations on fabric: silk and viscose.

You will also need: hidden separable zipper

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

SEAM ALLOWANCE: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front part yoke – 1 detail
2. Back part yoke – 1 detail
3. Front part - 1 detail
4. Back part - 1 detail
5. Waistband – 2 details

Cut pipings of 0.5 cm width by diagonal.

INSTRUCTIONS:

1. Gather front and back upper parts.
2. Fold pipings for front part yoke neckline, back part yoke and straps along the center and press. Sew folded pipings to edges of front part yoke neckline, back part yoke and yoke side edges; piping bent should be on the garment on 0.75 cm width. Cut seam allowances to 0.5 cm width. Turn a piping into wrong side, then topstitch along necklines, yoke side seams and straps.
3. Sew yokes to front and back parts.
4. Oversew front/back parts upper edges alongside with yokes.

5. Topstitch oversewn edges on the front and back parts.
6. Sew right side seam.
7. Press left sides of front and back parts into wrong sides and sew the zipper.
8. Gather front and back parts hem.
9. Sew the waistband to the blouse hem. Face waistband ends and topstitch the waistband along the joining seam.

TECHNICAL DRAWING:

