

Sewing Pattern — Lace blouse 5294

Recommendations on fabric: knitted fabric, lace.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

SEAM ALLOWANCE: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front part center - 1 detail
2. Front part side – 2 details
3. Back part center - 1 detail
4. Back part side - 2 details
5. Front sleeve part - 2 details
6. Back sleeve part - 2 details
7. Gusset – 2 details

OUR ADVICE: To make the fabric along stitched seams stretch, sew details with narrow zigzag or with special stretchable stitches. To make the hem stretch, oversew hem allowance with special oversewstitches (overlock), and then sew it using double needle. This is also attachable to other edges that should stay elastic.

These recommendations are not for industry.

INSTRUCTIONS:

1. Sew relieves into front and back parts.
2. Sew upper seam of the sleeve between neckline and notch.
3. Sew triangle gusset to front sleeve part.

4. Sew triangle gusset to back sleeve part.
5. Sew lower seams of the sleeves together.
6. Sew side seams.
7. Sew sleeves into armholes.
8. Oversew the neckline. Fold under the neckline, then topstitch.
9. Fold under sleeve and garment hems, then topstitch.

TECHNICAL DRAWING:

