

Sewing Pattern — Chiffon jacket 5292

Recommendations on fabric: embroidered chiffon.

You will also need: 1 button.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

SEAM ALLOWANCE: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front part - 1 detail
2. Back part - 1 detail
3. Sleeve - 2 details

Cut a piping of 0.5 cm width by diagonal.

INSTRUCTIONS:

1. Sew bust darts into front part.
2. Sew shoulder seams.
3. Sew side seams down to slits.
4. Sew sleeve seams.
5. Sew sleeves into armholes, fitting caps.
6. Fold pipings for back part slit and front part neckline along the center and press. Sew folded pipings to edges of back part slit, front part neckline and back part; piping bent should be on

the garment on 0.75 cm width. Cut seam allowances to 0.5 cm width. Turn pipings into wrong side, then topstitch the blouse along back part slit, front part neckline and back part.

7. Topstitch slits.

8. Fold under sleeve and garment hem allowances and topstitch.

9. Sew the button and a loop.

TECHNICAL DRAWING:

