

Sewing Pattern — Top 5285

Recommendations on fabric: natural or artificial knitted fabric.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

SEAM ALLOWANCE: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front part – 1 detail
2. Back part – 1 detail
3. Stand-up collar – 2 details
4. Back armhole facing – 1 detail
5. Front armhole facing – 1 detail
6. Side stripe – 2 details

Clue interfacing: front armhole facing, back armhole facing.

OUR ADVICE: To make the fabric along stitched seams stretch, sew details with narrow zigzag or with special stretchable stitches. To make the hem stretch, oversew hem allowance with special oversewstitches (overlock), and then sew it using double needle. This is also attachable to other edges that should stay elastic.

These recommendations are not for industry.

INSTRUCTIONS:

1. Strengthen front armhole facing and back armhole facing with clue interfacing
2. Sew back center seam.
3. Sew darts into front part and back part.
4. Oversew darts into the front part.
5. Sew side stripe to side back edge.

6. Sew side stripe to side front edge.
7. Sew shoulder edges, with braid between them.
8. Sew shoulder edges of front/back part facings.
9. Oversew lower edge of facings.
10. Sew side edges of front/back facings.
11. Face armhole with facing.
12. Turn the facing into the wrong side so that it folds the seam and makes the edging. Press the armhole.
13. Make decorative stitch along the armhole.
14. Sew facing outer edge to side and shoulder seams.
15. Overstitch the collar along the collar fall.
16. Sew collar center seam.
17. Make loops for the string on the outer collar.
18. Turn the inner collar into wrong side. Make stitches for the string into collar right side.
19. Sew the collar with the neckline.
20. Pull the string into the collar.
21. Oversew the hem.
22. Fold under the hem allowance and topstitch.

TECHNICAL DRAWING:

