

## Sewing Pattern — Shirt 5283

Recommendations on fabric: crinkle chiffon.

You will also need: clue interfacing; 5 buttons.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

SEAM ALLOWANCE: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Front part - 2 details
2. Back part – 1 detail
3. Sleeve - 2 details
4. Collar – 2 details
5. Stand-up collar – 2 details

Clue interfacing: placket, outer collar, stand-up collar.

### **INSTRUCTIONS:**

Press each stitched seam, then oversew and press again.

1. Strengthen the placket, outer collar, cuffs and stand-up collar with clue interfacing
2. Sew bust darts into front part and topstitch them.
3. Sew shoulder seams, then topstitch,
4. Sew sleeves into armholes, then topstitch seams.
5. Oversew separately side edges 15 cm from the hem, then sew downward to notch marks.

6. Press sleeve hem allowance in double into wrong side at 3 cm width. Topstitch it on foot width. Press sleeve hem allowance into wrong side again. Topstitch lower edge of the fold also on foot width.
7. Face the placket.
8. Stitch the inner collar with outer one. Turn collar right side out and topstitch.
9. Sew stand-ups, with the collar between them.
10. Sew inner stand-up (with the collar) to the neckline, fold the outer stand-up open edge under and topstitch along the seam of inner stand-up.
11. Press hem allowance to left, then topstitch. Press and topstitch slit allowances.
12. Make button holes into right (overlap) part and sew buttons to the left (underlap) one.

**TECHNICAL DRAWING:**

