

Sewing Pattern — Blouse 5282

Recommendations on fabric: linen or combined.

You will also need: clue interfacing, separable zipper.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

SEAM ALLOWANCE: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.

CUTTING:

Fabric:

1. Front part - 2 details
2. Back part – 1 detail
3. Front band - 2 details
4. Sleeve - 2 details
5. Cuff - 2 details
6. Collar – 2 details
7. Stand-up collar – 2 details

Clue interfacing: front band, outer collar, cuffs, stand-up collar.

INSTRUCTIONS:

1. Strengthen the front band, outer collar, cuffs and stand-up collar with clue interfacing.
2. Sew bust and waist darts into front part. Sew waist darts into back part.
3. Sew the zipper to front part edges.
4. Oversew inner edges of front bands. Face the front part with front band.
5. Turn front bands into wrong side and fold under. Oversew front part edges, press and topstitch them.
6. Make a stitch along the zipper sewing seam.
7. Sew shoulder seams.



8. Sew side seams.
9. Face inner collar with outer one, then turn over the collar.
10. Sew stand-ups together, with the collar between them.
11. Sew lower stand-up and collar with neckline, turn over the open edge of upper stand-up and topstitch into lower stand-up joining seam. Make decorative stitch along the collar. Sew font bands on shoulder seams with 1 cm stitch.
12. Sew sleeve seams.
13. Sew cuffs short edges in ring, with their right side together, cut the allowance near the notch, with split in the seam center. Fold cuffs along the center, right sides together, and sew split edges.
14. Sew the cuffs to sleeve hem line, oversew upper edge of the cuff together with the sleeve.
15. Topstitch the cuff joining seam on the sleeve, make decorative stitch along the cuff bottom and split edges.
16. Sew the sleeves into armholes fitting them around the sleeve cap.
17. Fold the hem allowance and topstitch it.

TECHNICAL DRAWING:

