

Sewing Pattern — Blouse 5281

Recommendations on fabric: natural or artificial chiffon.

You will also need: clue interfacing, 5 buttons.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

SEAM ALLOWANCE: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front part - 2 details
2. Back part - 1 detail
3. Front band - 2 details
4. Back part neckline facing – 1 detail
5. Right ruffle - 1 detail
6. Left ruffle – 1 detail
7. Sleeve - 2 detail
8. Sleeve ruffle – 2 details

Clue interfacing: front band, back part neckline facing.

INSTRUCTIONS:

1. Strengthen front band and back part neckline facing with clue interfacing.
2. Sew back part neckline facing to the front band.
3. Oversew inner edge of front band with facing.
4. Sew shoulder seams.

5. Sew side seams.
6. Sew front part left ruffle with front part right ruffle.
7. Oversew ruffle outer edge. Then turn over and topstitch.
8. Stitch the ruffle to edge of front part edge and back part neckline. Face the edges and back neckline with front band with facings. Turn front bands inside out. Sew front bands on shoulder seams with 1 cm stitches.
9. Oversew ruffle outer edge, then fold under and topstitch. Sew the ruffle to sleeve lower edge.
10. Sew sleeve seams.
11. Sew sleeves into armholes fitting around the sleeve caps.
12. Fold the hem under and topstitch.
13. Make buttonholes into right front part, sew buttons on the left one.

TECHNICAL DRAWING:

