

Sewing Pattern — Skirt 5272

Recommendations on fabric: soft cloth, wool crepe, gabardine.

You will also need: soft wool of 150 cm width; clue interfacing; zipper.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front panel facing - 1 folded detail
2. Back panel facing - 2 details
3. Back panel - 2 details
4. Front panel - 1 folded detail

Clue interfacing: strengthen facings with clue interfacing.

INSTRUCTIONS:

1. Sew darts into front and back panels, press towards center.
2. Sew back central seam from the zipper mark down to vent mark. Sew side seams. Sew zipper in.
3. Sew side seams of facings. Sew facing and waistline right sides together. Cut seam allowance closely to edge, fold into facing and topstitch along the edge. Fold facing into wrong side and sew to dart depths and seam allowance. Fold facing ends and sew to zipper bands.

4. Turn over hem allowance along hemline, press and topstitch. Press the one-piece lining of vent (back left panel) along bend line into wrong side and sew to hem. Sew lengthwise vent allowance (back right panel) as narrow as possible. Topstitch back left panel above the vent by diagonal, catching vent allowance.

TECHNICAL DRAWING:

