

## Sewing Pattern — Skirt 5271

Recommendations on fabric: light natural and combined material.

You will also need: Crepe of 150 cm width; clue interfacing; zipper; decorative buckle; eyelet details.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Fabric:

1. Hessian - 2 folded details
2. Pocket facing – 2 details
3. Side half belt – 1 detail
4. Belt loop - 1 detail
5. Back panel - 2 details
6. Front right panel - 1 detail
7. Front left panel - 1 detail
8. Back facing – 1 folded detail
9. Front right facing - 1 detail
4. Front left facing - 1 detail

Clue interfacing: strengthen back facing, front facings and pocket facings with clue interfacing.

### **INSTRUCTIONS:**

1. Strengthen back facing, front facings and pocket facings with clue interfacing (press thermal interfacing to left side with hot iron).
2. Sew darts into front and back panels and press them towards center.
3. Work slip pockets into back panels: press lining stripe of 4 cm width above pocket marking from

fabric back part work side. Press pocket facings along centre right side out. Pin the facing below pocket entrance line, with its edge corresponding to marked line; pin the Hessian above, with its edge corresponding to marking. Sew on 1 cm from line. Cut the panel alongside stitch toward stitch ends, by diagonal. Be careful with facings and Hessian! Press seam allowances into skirt. Fold the facings into wrong side so that appear precious framework; tack it. Topstitch accurately facing joining seam from right side. Fold small triangles at cot ends to wrong side and topstitch on facing precisely from one stitch ends to another one ends. From wrong side, sew free end of pocket Hessian to joining seam allowance. Press Hessian downwards, adjust and sew.

4. Sew back center seam down to slit mark. Press allowance apart. Topstitch slit edges. Sew side edges. Press allowance apart.

5. Sew facings together. Work waistline and figured half belt. Fold facings into wrong side, work and press.

6. Sew front center seam from the zipper mark downwards hem. Cut allowance near the mark: press lower parts into right panel and upper part into left one.

7. Sew zipper left band under left edge of zipper allowance. Coincide front center lines and topstitch with one stitch zipper right band and front panel joining seam allowance.

8. Turn over hem allowance along hemline, press and topstitch.

9. Work the nary and belt loop, fold them into right side, work and press. Insert the buckle into half belt and sew to skirt. Sew belt loop. Make eyelets into the half belt.

#### **TECHNICAL DRAWING:**

