

Sewing Pattern — Skirt 5268

Recommendations on fabric: wool or silk.

You will also need: Soft wool of 150 cm width; 1 zipper of 20 cm length; 1 button; clue interfacing for waistband.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

FABRIC:

1. Central part of front panel - 1 folded detail
2. Side part of front panel - 2 details
3. Back panel - 2 details
4. Waistband - 1 detail

Clue interfacing: strengthen the waistband with clue interfacing.

INSTRUCTIONS:

1. Sew front relief seams together. Press allowances toward the front panel middle part. Work a facing stitch on the relief seams of right side.
2. Sew back panel darts together.
3. Sew back center seam leaving the upper part of the seam free for zipper.
4. Sew zipper in.
5. Sew side seams together.

6. Sew waistband to waistline edge right side on left. Fold waistband along center break line right sides together; sew ends. Fold the band under the seam allowances of the open waistband overlapping the joining seam and topstitch closely along the edge. Work a button hole into the left end of the band and sew button to the right one.

7. Turn over hem allowance along hemline, press, then topstitch.

TECHNICAL DRAWING:

