

Sewing Pattern — Blouse 4202

Recommendations on fabric: natural or mixed, medium to high well draping stretch knit fabric

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowances: on hem – 1.5 cm, all other seams - 0.7 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.



When sewing the garment, pay attention to notches, they must match up with corresponding pieces.

CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Advice:

Knit fabric pieces are sewn together with special stretch-stitch or narrow zig-zag stitch. Seam allowance on hem is stitched with twin needles to save stretchiness. Pieces can also be sewn together with 3 or 4 – thread serger. When serging, cut seam allowances to 0.6 – 0.8 cm.

Fabric:

1. Back – 2 details
2. Front – 1 detail
3. Sleeve – 2 details

!

INSTRUCTIONS:

1. Put gathering stitch on curves (between lower notches) and lower edge of sleeve. Gather ruffle on lower edge. Approximate length of lower edge is mentioned on sleeve pattern piece.
2. Sew center edge of back. Serge seam allowance.
3. Sew right shoulder edge. Serge seam allowance.
4. Cut a bias tape of neckline length, width is 3.5 cm. Fold it in half lengthwise and stitch to neckline edge. Serge seam allowance. Overstitch lower edge of sleeve the same way.
5. Sew left shoulder edge. Serge seam allowance.
6. Sew in of sleeve, matching notches. Serge.
7. Sew side seams and seams of sleeve. Serge and press seam allowances.
8. Serge hem of garment. Turn onto wrong side, press and topstitch.

TECHNICAL DRAWING:

