

## Sewing Pattern — Skirt 5267

Recommendations on fabric: lightweight natural or mixed fibers

You will also need: crepe georgette of 150 cm width; 1 zipper; 4 buttons; 6 eyelets; fusible interfacing; tie

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 2 cm on hem, 1 cm on all other seams

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



### **CUTTING:**

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

#### Fabric:

1. Left panel - cut 1
2. Right panel - cut 1
3. Facing - cut 1

Fusible interfacing: facing

### **INSTRUCTIONS:**

1. Sew darts and press toward center.
2. Sew center back seam, press seam apart.
3. Serge outer edge of facing. Pin facing to right panel right sides together and sew. Clip into curves, understitch, turn onto wrong side, and press.

4. Serge front edge of left panel, press onto wrong side, and topstitch. Serge waistline edge, turn onto wrong side, and topstitch.
5. Press the pleat into the back panel, make or attach eyelets in accordance with marking and lace the tie through them.
6. On the right panel, make three main buttonholes and sew auxiliary button. On left panel, make one auxiliary buttonhole and sew main buttons.

**TECHNICAL DRAWING:**

