

Sewing Pattern — Pyjamas 5262

Recommendations on fabric: light silk or artificial material.

You will also need: sateen 150cm. in wide; iron-on interfacing;
3 buttons.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back – 2 pieces
2. Bust pocket – 1 piece
3. Lower pocket – 2 pieces
4. Collar – 2 pieces
5. Back facing- 1 folded piece
6. Front – 2 pieces
8. Sleeve – 2 pieces

Interfacing:

4. Collar – 2 pieces
5. Back facing - 1 folded piece
6. Front integrated facing – 2 pieces

INSTRUCTIONS:

1. Apply the interfacing to the collars, back and front facings.
2. Fold the pocket integrated facing to the right side and stitch the side edges. Turn it right side out. Press the seam allowances to the wrong side according to the pocket part. Edgestitch the top pocket edge. Topstitch the pocket to the garment.
3. Stitch the side/shoulder/sleeve edges. Press them open.

4. Join the facings across the shoulder seams. Press the seams open.
5. Make up and shape the collar.
6. Press the integrated facings to the right side of the garment front along the marked center front foldline. Place the collar between the facing and the neck edge and stitch it around the neck. Trim the seam allowances, clip the curves. Turn the facing to the wrong side, and press.
7. Stitch the sleeves to the garment.
8. Fold the short/sleeve hems to the wrong side and stitch in place.
9. Make buttonholes in the right front piece, sew buttons to the left piece.

TECHNICAL DRAWING:

