

Sewing Pattern — Set/Shorts 5255

Recommendations on fabric: lingerie jersey material.

You will also need: lingerie elastic.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



ADVICE: to prevent seam from stiffing, sew details with special (zigzag) stitch. To prevent hem from stiffing overcast it with overlocker and then stitch using double needle. Do the same for all edges must stay elastic.

The above is not for industrial manufacturing.

CUTTING:

Fabric:

1. Back - 2 pieces
2. Front - 2 pieces

INSTRUCTIONS:

1. Stitch the side/inside leg seams. Press the seams open.
2. With right sides together place one half of the pants inside other half and stitch the crotch seam leaving a slit above the fold marks (for the waist elastic).
3. Fold the waist self facing to the wrong side; fold the raw edge under and topstitch 0,1 cm above the foldline. Cut a piece of elastic to fit the waist, plus 2,5 cm. Thread the elastic through the casing. Overlap and stitch the elastic ends.
4. Stitch the elastic with zigzag stitch to the leg openings stretching it slightly and placing it 0,2 cm out of the marks. Fold the seam allowances to the wrong side of the garment and topstitch them with zigzag (stretching it slightly).

TECHNICAL DRAWING:

