

Sewing Pattern — Set/Top 5254

Recommendations on fabric: elastic or jersey material for lingerie.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



ADVICE: to prevent seam from stiffing, sew details with special (zigzag) stitch. To prevent hem from stiffing overcast it with overlocker and then stitch using double needle. Do the same for all edges must stay elastic.

The above is not for industrial manufacturing.

CUTTING:

Fabric:

1. Shoulder strap – 2 pieces
2. Back – 1 folded piece
3. Front – 1 folded piece
4. Back facing - 1 folded piece
5. Front facing - 1 folded piece

INSTRUCTIONS:

1. Stitch the side/shoulder seams. Stitch the pieces of facings together.
2. Press the long strap edges allowances to the wrong side and topstitch them. Make pleats on the short strap's edges. Tack the straps to the garment according to the marks.
3. With right sides together, stitch the facing to the neck edge. Fold the facing to the wrong side and topstitch it.
4. Fold the hem to the wrong side and stitch in the place.

TECHNICAL DRAWING:

