

Sewing Pattern — Set 5250

Recommendations on fabric: thick natural or synthetic silk.

You will also need: atlas (sateen), lingerie elastic tape, hook-and-eye tape.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Shoulder strap – 4 pieces
2. Side/back band – 2 folded pieces
3. Side cup – 4 pieces
4. Centre cup – 2 folded pieces
5. Centre triangle – 2 folded pieces

INSTRUCTIONS:

1. Sew the shoulder straps: fold the pieces in half lengthways, right sides together, and stitch along the edges leaving one edge open. Turn the straps right side out. Then press and topstitch close to the edges.
2. Stitch the side/centre pieces of the cups. Fold the front pieces of the cups inside and overstitch the top/front/lower edges placing the shoulder straps between. Turn the cups right side out, tack them and press slightly.
3. Fold the pieces of the band in half lengthways right sides inside and stitch along the long edges. Turn the bands right side out and press them. Sew the bands to the cups.
4. Stich the top/bottom edges of centre triangle pieces right sides together. Turn the triangle right side out and press it.
5. Push the elastic tape inside the bands through the openings up to the marks. Fix the edges to the garment. Sew the hook-and-eye tape to the band ends.
6. Try the bra on, check the shoulder strap lengths and stitch them to the garment.

TECHNICAL DRAWING:

