

Sewing Pattern — Chemise 5248

Recommendations on fabric: natural or mixed silk material
150 cm (59-60 in.) width.

You will also need: ribbon or lace for the trim around cups.

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 1 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Fabric:

1. Upper Back – cut 1 on fold
2. Lower back – cut 2
3. Outer front cup – cut 2
5. Lower front –cut 1 on fold

Trim:

4. Inner front cup – cut 2
6. Back facing – cut 1
7. Shoulder strap – cut 2

INSTRUCTIONS:

1. Sew center lower back seam. Serge seam and press toward left. Sew the lower and upper backs together. Serge seam and press upward. Topstitch the seam allowances to the upper back.
2. Sew the darts on outer and inner cups, pin the cups, right sides together, and sew the top and center edges. Turn right side out and press. Topstitch trim to the upper edges. Sew the cups to the lower front at marks.
3. Sew side seams.
4. Sew the shoulder straps to the back at placement marks. Sew the back facing, right sides together, to the upper back. Turn under and press. Slipstitch side edges of back facing to side seam. Topstitch.
5. Try the chemise on, check the length of the shoulder strap and tack to the garment front.

TECHNICAL DRAWING: