

Knit Blouse - Sewing Pattern #2059

Recommendations on fabric: natural/mixed knit fabric of medium stretchiness.

You will also need: closure - buckle; knit bias tape.

Seam allowances: seam allowance for hem of garment - 2.0 cm, front neckline edge and lower edge yokes - 0 cm, other seams - 1.0 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Front - cut 1 on fold
2. Back - cut 2
3. Front yoke - cut 2
4. Stand collar - cut 2

INSTRUCTIONS:

1. Sew front darts (if drafted for the size measurements provided). Press bulk towards top.
2. Sew the center back seam. Serge the seam allowances and press towards left.
3. Finish the slit of front neckline with bias tape. Serge upper edges of front. Finish the lower edges of front yokes with the bias tape. Pin yokes onto upper edge of front and topstitch into the seam of the bias tape finishing the edge.
4. Sew shoulder and side seams, press towards the back and serge.
5. Pin stand collars together right sides together and sew along the upper edge, inserting the buckle closure. Clip into curves, turn right side out and press. Sew outer stand collar into neckline, press the seam allowance at stand collar. Fold under the seam allowance of the inner side inside at 1 cm and topstitch into seam of.
6. Cut (or take ready) bias tape , its width should equal 4 cm and length should equal the length of armhole + 6 cm. Fold bias tape in half lengthwise right side out and press. Pin bias tape to armhole edge from the right side and sew. Fold bias tape onto wrong side, clip into seam allowances and topstitch onto main piece along the seam. Press seam.
7. Serge the lower edge of garment, press onto wrong side and topstitch.

TECHNICAL DRAWING:

