

Skirt With Shaped Yoke - Sewing Pattern #2066

Recommendations on fabric: natural/mixed fabric suitable for dresses.

You will also need: fusible interfacing; 1 dress zipper.

Seam allowances: all seams 1 cm. Seam allowance for hem of garment – 1.5 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back yoke – cut 1
2. Front yoke – cut 2
3. Skirt gore – cut 6
4. Belt – cut 1

Fusible interfacing:

1. Belt – cut 1

INSTRUCTIONS:

1. Apply fusible interfacing to belt.
2. Serge upper edges of gores. Serge lower edge of back yoke. Sew gores to back yoke (start and stop stitching exactly at the marked line of the gores seam), press seam. Sew gores together, serge and press.
3. Serge lower edge of front yoke. Sew gores to front yoke (start and stop stitching exactly at the marked line of the gores seam), press seam. Sew gores together, serge and press.
4. Serge left side edges separately. Sew left side seam from zipper mark down to hem. Seam Allowances шва press apart. Sew in zipper. Sew right side edge, serge and press.
5. Fold belt in half lengthwise right sides together and sew shorter edges and the end, clip into seam allowance near the notch. Turn belt right side out, press. Sew outer edge of belt to skirt, fold under the seam allowance of the inner side inside and topstitch into seam of.
6. Serge lower edge of skirt, press onto wrong side and topstitch.
7. Make buttonhole on belt and sew on a button.

TECHNICAL DRAWING:

