

Skirt With Wrap Effect - Sewing Pattern #2084

Recommendations on fabric: thin natural/mixed suiting fabrics.

You will also need: fusible interfacing; 1 dress zipper.

Seam allowances: all seams 1 cm. Seam allowance along lower edge of front and left skirts – 3 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back – cut 2
2. Front skirt – cut 2
3. Back facing – cut 2
4. Front facing – cut 1

Fusible interfacing:

1. Back facing – cut 2

2. Front facing – cut 1

INSTRUCTIONS:

1. Apply interfacing to facings.
2. Sew darts on Backs, press the inner part towards center. Serge center edges of the back skirt separately. Sew center seam from notch for zipper to hem. Seam Allowances $\frac{1}{4}$ " press apart. Sew in zipper.
3. Serge slanted edge of front skirt. Fold one-piece center front facing onto right side and sew the lower corner. Turn center front facing onto wrong side, press. Pin right skirt not left skirt, matching center lines, and topstitch along the marked line.
4. Sew side seams, press seam allowances towards back and serge.
5. Sew side edges of facings, press the seam apart. Serge lower edge. Pin facing to garment right sides together and sew upper edge. Topstitch seam allowances onto facing at 0.2 cm from the seam. Fold facing onto wrong side, press. Fold inside the middle edges facings and sew to zipper tape. Slipstitch facing to side seams as well.
6. Serge lower edge of skirt, press onto wrong side and finish with hidden stitches.

TECHNICAL DRAWING:

