Skirt With Pleats - Выкройка #2132

Recommendations on fabric: natural/mixed fabric suitable for dresses in contrasting colors.

You will also need: fusible interfacing; 1 dress zipper; 2 decorative of the zipper.

Seam allowances: all seams 1 cm. Seam allowance for hem of garment – 1.5 cm.



О припусках на швы::
- Если на выкройке двойной контур, припуски на швы уже включены. Они составляют 1 см, если не указано иначе.
- Если у выкройки одинарный контур, припуски на швы не включены, и должны быть добавлены при раскрое.

О требуемой длине ткани:
Внимание! В инструкциях не указано необходимое количество ткани, так как оно зависит от ширины и рисунка ткани, а также Ваших размерных признаков. Прежде всего, распечатайте лекала и разложите их на ширине, соответствующей ширине ткани, которую Вы хотите использовать (обычно от 90 до 150 см), чтобы определить, сколько ткани Вам потребуется. Не забывайте учитывать парные детали и детали со сгибом.

РАСКРОЙ:

Обратите внимание при раскрое:
Обратите внимание на обозначение долевой нити при раскладке деталей. Некоторые детали кроятся со сгибом. Это указано на лекале. Перенесите все отметки и другие особенности дизайна (вытачки и т.п.) с лекала на ткань.
При стачивании деталей, обращайте внимание на надсечки, они должны совпадать.

Main fabric:
1. Back skirt – cut 2
2. Front skirt – cut 1 on fold
3. Underlay piece – cut 2

Decorative fabric:
1. Back yoke – cut 4
2. Front yoke – cut 2

3. Facing – cut 4

Fusible interfacing:
1. Back yoke – cut 2
2. Front yoke – cut 1
3. Facing – cut 4

Инструкции:

1. Apply fusible interfacing.

2. Make and baste pleats on back skirt (fold bulks from center). Sew back yoke to back skirt, press towards top. Serge center edges of the back skirt separately. Sew center seam from notch for zipper to hem. Seam Allowances шва press apart. Sew in zipper.

3. Mark the position of pocket. Fold pocket facings in half wrong sides together and press. Make auxiliary lines on facings. Make auxiliary lines parallel to the pocket opening. Sew facings to front. Finish stitching at the guidance lines that you marked near pockets. Check your work on the wrong side (stitch lines should be parallel). Slash pocket opening on the side front. Snip diagonally toward end of stitching at 1-1.5 cm from end of pocket opening. Turn facings onto wrong side through the resulting opening, straighten edges. Sew a double back stitch lines near corners to fix ends of pockets. Insert zipper tape under facing in such a way that the teeth are visible and sew. Serge the underlay piece around all edges. Pin the underlay on the facings from the wrong side and topstitch into seam of facings.

4. Make and baste pleats on front skirt (fold bulks from center). Sew front yoke to front skirt, press towards top.

5. Sew side seams, press towards the back and serge.

6. Sew side seams of inside yokes, press the seam apart. Serge lower edge. Pin yoke onto skirt right sides together and sew upper edge. Seam Allowances topstitch at the yoke at 0.2 cm from the seam. Fold yoke onto the wrong side, press. Fold inside the middle edges and sew to zipper tape. Topstitch yoke into the seam of outer yoke (stitch-in-the-ditch).

7. Serge lower edge of skirt, press onto wrong side and topstitch.

Технический рисунок:



