

Hoodie - Sewing Pattern #2159

Recommendations on fabric: natural/mixed fabrics suitable for raincoats.

You will also need: separating zipper; elastic tape, its width should equal 4 cm, its length should be 4 cm shorter than the hem placket.

Seam allowances: Outer seam allowance of the hood - 3 cm, all other seams - 1 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Front - cut 2
2. Back - cut 1 on fold
3. Placket center front facings - cut 4
4. Hem placket - cut 1 on fold
5. Sleeve placket - cut 2

6. Hood - cut 2

INSTRUCTIONS:

1. Sew shoulder and side seams. Serge seams and press towards back.
2. Fold hem placket in half lengthwise right side out and sew to the lower edge of the jacket, serge and press towards top. Thread elastic tape into the placket and slipstitch to the center front edge.
3. Sew the outer placket to the center front edge, press seam allowance towards the placket. Sew the zipper to the outer placket. Pin inner placket onto the outer placket and sew the corners and the center front edge, start and stop stitching exactly at the marked seam line. Fold the inner placket onto the wrong side. Fold inside the seam allowance and topstitch into seam of. Sew a decorative stitch along the center front edge at 1 cm from the zipper.
4. Sew the sleeve placket into a ring. Pin together in half lengthwise and press. Sew the outer side of the placket to the sleeve. Fold under the seam allowance of the inner side inside topstitch into seam of.
5. Sew hood seam. Serge. Fold under the outer edge of the hood, then at 2 cm and topstitch. Sew the hood to the jacket. Serge, press towards the front and towards the back.

TECHNICAL DRAWING:

