Dress With Zipper Imitation - Выкройка #2176



Recommendations on fabric: thick natural/mixed knit fabric of small stretchiness.

You will also need: knit fusible interfacing; separating zipper.

Seam allowances: all seams 1 cm. Seam allowance for hem of garment and hem of sleeve – 1.5 cm.

О припусках на швы::
- Если на выкройке двойной контур, припуски на швы уже включены. Они составляют 1 см, если не указано иначе.
- Если у выкройки одинарный контур, припуски на швы не включены, и должны быть добавлены при раскрое.

О требуемой длине ткани:
Внимание! В инструкциях не указано необходимое количество ткани, так как оно зависит от ширины и рисунка ткани, а также Ваших размерных признаков. Прежде всего, распечатайте лекала и разложите их на ширине, соответствующей ширине ткани, которую Вы хотите использовать (обычно от 90 до 150 см), чтобы определить, сколько ткани Вам потребуется. Не забывайте учитывать парные детали и детали со сгибом.

О работе с эластичными тканями:
Детали выкройки из трикотажа стачиваются специальным эластичным швом или швом зигзаг. Припуск на подгибку низа может быть настрочен двойной иглой для сохранения эластичности. Детали также можно стачать при помощи оверлока. При стачивании оверлоком, пожалуйста, обрежьте припуски на швы до ширины 0.6 - 0.8 см.

РАСКРОЙ:

Обратите внимание при раскрое:
Обратите внимание на обозначение долевой нити при раскладке деталей. Некоторые детали кроятся со сгибом. Это указано на лекале. Перенесите все отметки и другие особенности дизайна (вытачки и т.п.) с лекала на ткань.
При стачивании деталей, обращайте внимание на надсечки, они должны совпадать.

Main fabric:
1. Back – cut 2
2. Back yoke – cut 2

3. Front – cut 2
4. Front yoke – cut 2
5. Sleeve – cut 2
6. Back facing – cut 2
7. Front facing – cut 2

Fusible interfacing:
1. Back facing – cut 2
2. Front facing – cut 2

Инструкции:

1. Apply fusible interfacing.

2. Sew darts on front, if the size implies these, press bulk towards top.

3. Sew center seam on back yoke, press towards left, serge. Sew center seam on front yoke, press towards left, serge. Sew shoulder seams, press towards the back, serge.

4. Sew center back seam, press towards left, serge. Sew center front seam, inserting the right side of zipper between the pieces, press seam allowances to the right, serge. Sew a decorative stitch along the seam at 0.5 cm. Topstitch the left side of zipper onto Front.
5. Sew sleeves to back, press seam allowances towards sleeve and serge. Sew sleeves to front, press seam allowances towards sleeve and serge.

6. Pin yoke to the garment and sew around, press seam allowances towards yoke and serge. Sew a decorative stitch along the seam at 0.5 cm.

7. Sew side seams processing the sleeve seam at the same time, serge and press.

8. Sew center edges of facings, sew shoulder edges of facings, press the seam apart. Serge lower edge. Pin facing to garment right sides together and sew the neckline. Fold the facing onto the wrong side, straighten, press. Slipstitch facing to the seam allowances of center and shoulder seams.

9. Seam allowance along hem of garment and hem of sleeve serge, press onto wrong side and topstitch.

Технический рисунок:

