

Tunic With Yoke - Sewing Pattern #2220

Recommendations on fabric: natural/mixed knit fabric of small stretchiness.

You will also need: knit fusible interfacing; 6 buttons.

Seam allowances: all seams 1 cm; seam allowance for hem of garment – 2.0 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.

Note on working with stretchy fabric:

Knitted fabric pieces are sewn together with special elastic or narrow zig-zag stitch. Seam allowance on hems can be stitched with twin needles to save stretchiness. Pieces can also be sewn together with a serger. When serging, cut seam allowances to 0.6 – 0.8 cm.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back yoke - cut 1
2. Back - cut 1 on fold

3. Front - cut 1 on fold
4. Front yoke - cut 2
5. Sleeve - cut 2
6. Cuff - cut 2

Fusible interfacing:

1. Cuff - cut 2

INSTRUCTIONS:

1. Apply fusible interfacing to cuffs and one-piece center front facing on front yoke.
2. Sew darts on front, press bulk towards top.
3. Sew back yoke to yoke, press seam allowances down and serge.
4. Serge the vertical edge of the one-piece center front facing of the front yoke. Fold the one-piece center front facing on the front yoke onto front side and sew upper corner. Trim corner, turn the piece right side out, straighten, press. Make buttonholes on right yoke. Pin right yoke onto left yoke, matching center lines, and baste together along lower edge.
5. Sew front yoke to front, press seam allowances down and serge.
6. Sew side and shoulder seams, press towards the back and serge.
7. Cut (or take ready) bias tape, its width should equal 4 cm and length should equal the length of neckline + 4 cm. Fold bias tape in half lengthwise right side out and press. Pin bias tape to neckline from the right side, leaving loose ends, and sew. Fold bias tape onto wrong side, clip into seam allowances and topstitch onto main piece along the seam. Press seam.
8. Sew sleeve seam, press towards the back and serge. Sew sleeves into armholes matching notches and adjusting ease, serge and press.
9. Fold cuff in half lengthwise right sides together and sew short sides. Turn right side out, straighten, press. Make buttonholes on the outer side of cuff. Pin outer side of cuff onto inner side of cuff, matching notches, and baste together along edge. Sew the cuff to the sleeve, matching notches, press seam allowances towards sleeve and serge.
10. Serge bottom edge of garment, press onto wrong side and topstitch.
11. Sew on buttons on the left yoke and on cuffs.

TECHNICAL DRAWING:

