

## Jacket Without Lining - Sewing Pattern #2277

Recommendations on fabric: natural/mixed suiting fabric.

You will also need: fusible interfacing; 3 buttons.

Seam allowances: all seams 1 cm. Seam allowance for hem of garment – 3 cm.

### Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

### Note on length of fabric:

*Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.*



## CUTTING:

### Note on cutting:

*On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.*

*When sewing the garment, pay attention to notches, they must match up.*

Main fabric:

1. Side back – cut 2
2. Center back – cut 2
3. Center front – cut 2
4. Side front – cut 2
5. Back neck facing – cut 1
6. Center front facing – cut 2
7. Cuff – cut 2

8. Belt Loop – cut 1
9. Belt – cut 1

Fusible interfacing:

1. Back neck facing – cut 1
2. Center front facing – cut 2
3. Belt – cut 1
4. Cuff – cut 2

## INSTRUCTIONS:

1. Apply fusible interfacing.
2. Sew side backs to center back. Serge seams and press towards center. Sew center back seam. Serge the seam allowances and press towards left.
3. Sew side fronts to center front. Serge seams and press towards center.
4. Sew shoulder and side seams of jacket sewing the sleeve edges at the same time. Serge seams and press towards back.
6. Sew and press apart the shoulder edges of the back neckline facing and of the center front facing. Serge the outer edge.
7. Pin center front facing onto front, right sides together, and sew along the hem, center front edge, lapel, back neckline. Clip seam allowances, trim away corner. Center front facing and fold facing onto wrong side and press. Slip stitch facing to shoulder seams.
8. Sew cuff into a ring, press the seam allowances apart. Pin cuff to garment right sides together and sew cuff to garment. Fold cuff onto wrong side and press. Turn under the inner edge and topstitch onto sleeve. Fold away hem of sleeve onto right side, straightening the cuff.
9. Serge the hem of jacket, fold inside onto wrong side and topstitch.
10. Serge one longer edge of the belt loop. Fold belt loop so that it has 3 layers in total and topstitch along longer sides. Cut belt loop into 4 pieces. Topstitch belt loops onto princess seams at the waist level.
11. Make buttonholes on right front, and sew on buttons onto left front.
12. Fold belt in half lengthwise right sides together and sew, and leave an opening unsewn along the lower edge, so that you can turn out the piece later. Turn belt right side out, straighten and press. Sew the opening closed.

**TECHNICAL DRAWING:**

