Blouse With Trimming - Выкройка #2301



Recommendations on fabric: natural/mixed fabrics suitable for blouses/dresses in 2 contrasting or matching colors.

You will also need: fusible interfacing; dress zipper.

Seam allowances: all seams 1 cm.

О припусках на швы::
- Если на выкройке двойной контур, припуски на швы уже включены. Они составляют 1 см, если не указано иначе.
- Если у выкройки одинарный контур, припуски на швы не включены, и должны быть добавлены при раскрое.

О требуемой длине ткани:
Внимание! В инструкциях не указано необходимое количество ткани, так как оно зависит от ширины и рисунка ткани, а также Ваших размерных признаков. Прежде всего, распечатайте лекала и разложите их на ширине, соответствующей ширине ткани, которую Вы хотите использовать (обычно от 90 до 150 см), чтобы определить, сколько ткани Вам потребуется. Не забывайте учитывать парные детали и детали со сгибом.

РАСКРОЙ:

Обратите внимание при раскрое:
Обратите внимание на обозначение долевой нити при раскладке деталей. Некоторые детали кроятся со сгибом. Это указано на лекале. Перенесите все отметки и другие особенности дизайна (вытачки и т.п.) с лекала на ткань.
При стачивании деталей, обращайте внимание на надсечки, они должны совпадать.

Main fabric:
1. Back - cut 2
2. Front - cut 1
3. Side front - cut 1
4. Sleeve - cut 2
5. Back neck facing – cut 2
6. Front neck facing – cut 1

Main fabric 1:
1. Cuff - cut 2
2. Front decoration – cut 2
3. Side front decoration – cut 2
4. Back decoration – cut 2

Fusible interfacing:
1. Back neck facing – cut 2
2. Front neck facing – cut 1
3. Cuff - cut 2

Инструкции:

1. Apply fusible interfacing.

2. Serge center back edges separately on each piece. Sew center seam from notch for zipper down to hem, press the seam apart. Sew in zipper.

3. Sew darts on front. Press bulk towards top.

4. Sew shoulder seams, press towards the back and serge.

5. Serge upper edges of inner decorations.

6. Pin side decorations together right sides together and sew lower edge. Turn pieces right side out and press. Sew outer decoration to side front. Press towards trimming. Topstitch inner decoration into the seam of outer decoration.

7. Pin front decorations together right sides together and sew lower edge. Turn right side out and press. Sew outer decoration to the lower edge of front. Press towards trimming. Pin front onto side part and topstitch front into the seam of decoration up to the side seam.

8. Pin back decorations right sides together and sew lower edge. Turn right side out and press. Sew outer decoration to the lower edge of back. Press towards trimming. Pin front onto back, right sides together, and sew side seams. Topstitch back decoration into the seam of outer decoration.

9. Sew the shoulder seams of the neckline facings, press the seam apart. Serge the outer edge. Pin facing to garment right sides together and sew the neckline. Clip into curves, turn facing onto wrong side, straighten, press. Slipstitch to shoulder seams and to zipper tape.

10. Sew sleeve seam, press towards the back and serge. Sew sleeves into armholes, matching notches, serge.

11. Sew cuff into a ring, press the seam apart. Fold cuff in half lengthwise and press right side out. Sew cuff to

wrong side of sleeve, serge.

Технический рисунок:

