Denim Top - Выкройка #2333

Recommendations on fabric: thick natural/mixed fabric suitable for dresses with elastane. Denim.



You will also need: fusible interfacing, 2 buttons.

Seam allowances: seam allowance for hem of garment — 1.5 cm, along hem of sleeve – 2 cm, other seams 1 cm.

О припусках на швы::
- Если на выкройке двойной контур, припуски на швы уже включены. Они составляют 1 см, если не указано иначе.
- Если у выкройки одинарный контур, припуски на швы не включены, и должны быть добавлены при раскрое.

О требуемой длине ткани:
Внимание! В инструкциях не указано необходимое количество ткани, так как оно зависит от ширины и рисунка ткани, а также Ваших размерных признаков. Прежде всего, распечатайте лекала и разложите их на ширине, соответствующей ширине ткани, которую Вы хотите использовать (обычно от 90 до 150 см), чтобы определить, сколько ткани Вам потребуется. Не забывайте учитывать парные детали и детали со сгибом.

РАСКРОЙ:

Обратите внимание при раскрое:
Обратите внимание на обозначение долевой нити при раскладке деталей. Некоторые детали кроятся со сгибом. Это указано на лекале. Перенесите все отметки и другие особенности дизайна (вытачки и т.п.) с лекала на ткань.
При стачивании деталей, обращайте внимание на надсечки, они должны совпадать.

Main fabric:
1. Back – cut 2
2. Center back belt — cut 2
3. Side back belt — cut 2
4. Front — cut 2
5. Center front belt — cut 2
6. Side front belt — cut 2
7. Sleeve — cut 2

8. Collar — cut 2
9. Center front facing — cut 2
10. Back neck facing – cut 1

Fusible interfacing:
1. Collar — cut 1
2. Center front facing — cut 2
3. Back neck facing – cut 1

Инструкции:

1. Apply fusible interfacing.

2. Sew darts on back, press the inner part towards center. Sew the center back seam, seam allowance press towards left and serge.

3. Sew center back belt to side back belt, press seam allowances towards center, serge. Sew a decorative stitch along the seam at 0.5 cm. Sew back belt to upper part, press the seam allowance at belt and serge.

4. Sew a gathering stitch along lower edge of upper front between the markings and gather fullness.

5. Sew center front belt to side front belt, press seam allowances towards center, serge. Sew a decorative stitch along the seam at 0.5 cm. Sew front belt to upper piece, press seam allowances towards belt and serge.

6. Pin collars together, right sides together, and sew collar ends and collar fall. Start and stop sewing exactly at the marked line of the seam between collar and garment. Trim away corners, snip into seam allowance near the mark. Turn the collar right side out, straighten and press.

7. Sew shoulder edges of the garment, press towards the back and serge. Sew side seams of back neckline facing and central front facings, press seam apart. Serge the outer edge.

8. Place center front facing onto front right sides together, pin together and sew along the center front edge. Sew upwards up to the notch marking the end of collar seam. Trim away corners. Turn center front facings right side out, straighten seams.

9. Sew lower collar into the neckline of the main piece, sew upper collar into the neckline of back facing and center front facing. Snip into seam allowances of collar, press apart and slipstitch together close to the seam. Sew a decorative stitch along the edge center front facings, of lapel and of collar at 0.5 cm.

10. Sew side seams, press towards the back and serge. Sew a decorative stitch along upper edge of belt at 0.5 cm.

11. Sew a gathering stitch along a sleeve cap and gather fullness. Sew sleeve seam, press the seam apart. Sew

sleeves into armholes, serge and press.

12. Serge hem of garment and lower edge of sleeve, press onto wrong side and topstitch. Sew a decorative stitch along the lower edge of belt and the lower edge of sleeve at 1 cm.

13. Make buttonholes on right part of belt. Sew on buttons at left belt.

Технический рисунок:

