Skirt With Wrap - Выкройка #2389

Recommendations on fabric: thick natural/mixed knit fabric with medium stretchiness.



You will also need: knit fusible interfacing; 1 dress zipper.

Seam allowances: all seams 1 cm. Seam allowance for hem of garment – 3 cm.

О припусках на швы::
- Если на выкройке двойной контур, припуски на швы уже включены. Они составляют 1 см, если не указано иначе.
- Если у выкройки одинарный контур, припуски на швы не включены, и должны быть добавлены при раскрое.

О требуемой длине ткани:
Внимание! В инструкциях не указано необходимое количество ткани, так как оно зависит от ширины и рисунка ткани, а также Ваших размерных признаков. Прежде всего, распечатайте лекала и разложите их на ширине, соответствующей ширине ткани, которую Вы хотите использовать (обычно от 90 до 150 см), чтобы определить, сколько ткани Вам потребуется. Не забывайте учитывать парные детали и детали со сгибом.

О работе с эластичными тканями:
Детали выкройки из трикотажа стачиваются специальным эластичным швом или швом зигзаг. Припуск на подгибку низа может быть настрочен двойной иглой для сохранения эластичности. Детали также можно стачать при помощи оверлока. При стачивании оверлоком, пожалуйста, обрежьте припуски на швы до ширины 0.6 - 0.8 см.

РАСКРОЙ:

Обратите внимание при раскрое:
Обратите внимание на обозначение долевой нити при раскладке деталей. Некоторые детали кроятся со сгибом. Это указано на лекале. Перенесите все отметки и другие особенности дизайна (вытачки и т.п.) с лекала на ткань.
При стачивании деталей, обращайте внимание на надсечки, они должны совпадать.

Main fabric:
1. Back skirt – cut 2
2. Back yoke – cut 4

3. Front right skirt – cut 1
4. Front left skirt – cut 1
5. Front yoke – cut 2
6. Trimming – cut 2

Fusible interfacing:
1. Back yoke – cut 2
2. Front yoke – cut 1
3. Trimming – cut 1

Инструкции:

1. Apply fusible interfacing to inner yokes.

2. Sew darts on back. Press bulk towards center. Sew back yoke to back skirt, press towards top. Serge center edges of the back skirt separately. Sew center seam from notch for zipper to hem. Seam Allowances шва press apart. Sew in zipper.

3. Pin trimmings right sides together and sew the outer and the lower edges. Fold inner trimming onto wrong side and press. Sew trimming to right skirt. Serge and press towards the main piece. Serge the outer edge of the left part, press onto wrong side and topstitch. You may also finish the edge with bias tape, int this case trim away seam allowance leaving 0.5 cm, finish the edge, turn inside and topstitch.

4. Pin right skirt onto left skirt, matching along the upper edge and the side edges. Treat as one piece in the future. Sew front yoke to front skirt, press towards top.

5. Sew side seams, press towards the back and serge.

6. Sew side seams of inside yokes (further referred to as - of facings), press the seam apart. Serge lower edge. Pin facing to skirt right sides together and sew upper edge. Topstitch seam allowances onto facing at 0.2 cm from the seam. Turn facing under, press. Fold inside the middle edges facings and sew to zipper tape. Stitch-in-the-ditch the facing into the seam of outer yoke.

7. Serge lower edge of skirt, press onto wrong side and finish with hidden stitches.

Технический рисунок:



