

Skirt With Wrap - Sewing Pattern #2397

Recommendations on fabric: natural/mixed suiting fabrics.

You will also need: fusible interfacing; 1 button; dress zipper; decorative buckle.

Seam allowances: all seams 1 cm. Seam allowance along the slanted edges of fly skirts – 0 cm; seam allowance along the lower edges – 3 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back – cut 2
2. Front right skirt – cut 1
3. Front left skirt – cut 1
4. Inner skirt – cut 1 on fold
5. Belt – cut 1
6. Fly belt – cut 1

7. Buckle belt – cut 1

Fusible interfacing:

1. Belt – cut 1
2. Fly belt- cut 1
3. Buckle belt – cut 1

INSTRUCTIONS:

1. Apply fusible interfacing to belt. Apply fusible interfacing to the one-piece plackets of front fly skirts.
2. Sew darts on back, press the inner part towards center. Serge the center edges of back skirts separately. Sew center edge from notch for zipper to bottom. Sew in zipper.
3. Serge the outer edge of one-piece plackets on fly pieces, press onto wrong side and topstitch.
4. Sew darts on inner skirts, press bulk towards center. Serge the seam allowance along the hem, fold inside onto wrong side and topstitch.
5. Pin left skirt onto inner skirt and baste together along the side edges and the upper edge. Pin right fly skirt onto left fly skirt and baste together along the side edge and the upper edge.
6. Sew side seams, press seam allowances towards back and serge.
7. Fold belt in half lengthwise, right sides together and sew the shorter side and the corner. Start stitching exactly at the marked line of seam between belt and skirt. Clip into seam allowances near the notch, belt turn right side out and press. Sew outer edge of belt to upper edge, turn inner edge under and topstitch into seam of.
8. Fold fly belt in half lengthwise, right sides together and sew longer and one shorter edge. Trim away corners, turn belt right side out, straighten, press. Serge shorter edge. Topstitch the fly belt onto the left side of belt, placing the finished edge towards the left side seam. Fold the buckle belt in half lengthwise right sides together and sew long edge. Turn right side out and press. Fold in half, insert eh buckle and topstitch onto belt on the left, folding under the raw seam allowances.
9. Serge lower edge of skirt, press onto wrong side and topstitch.
10. Make a button hole on the shorter part of the belt. Sew on a button correspondingly button loops.

TECHNICAL DRAWING:

