# Dress With Wrap Effect - Выкройка #2416




Recommendations on fabric: natural/mixed knit fabric of small stretchiness in contrasting or similar color.

You will also need: knit fusible interfacing.

Seam allowances: all seams 1 cm; seam allowance for hem of garment and hem of sleeve – 2.0 cm.

**О припусках на швы::**
*- Если на выкройке двойной контур, припуски на швы уже включены. Они составляют 1 см, если не указано иначе.*
*- Если у выкройки одинарный контур, припуски на швы не включены, и должны быть добавлены при раскрое.*

**О требуемой длине ткани:**
*Внимание! В инструкциях не указано необходимое количество ткани, так как оно зависит от ширины и рисунка ткани, а также Ваших размерных признаков. Прежде всего, распечатайте лекала и разложите их на ширине, соответствующей ширине ткани, которую Вы хотите использовать (обычно от 90 до 150 см), чтобы определить, сколько ткани Вам потребуется. Не забывайте учитывать парные детали и детали со сгибом.*

**О работе с эластичными тканями:**
*Детали выкройки из трикотажа стачиваются специальным эластичным швом или швом зигзаг. Припуск на подгибку низа может быть настрочен двойной иглой для сохранения эластичности. Детали также можно стачать при помощи оверлока. При стачивании оверлоком, пожалуйста, обрежьте припуски на швы до ширины 0.6 - 0.8 см.*

## РАСКРОЙ:

**Обратите внимание при раскрое:**
*Обратите внимание на обозначение долевой нити при раскладке деталей. Некоторые детали кроятся со сгибом. Это указано на лекале. Перенесите все отметки и другие особенности дизайна (вытачки и т.п.) с лекала на ткань.*
*При стачивании деталей, обращайте внимание на надсечки, они должны совпадать.*

Main fabric:
1. Back - cut 1 on fold
2. Front right - cut 1
3. Back neck facing - cut 1
4. Front neck facing - cut 1

5. Belt right – cut 1

Main fabric 1:
1. Front left - cut 1
2. Sleeve - cut 2
3. Belt left – cut 1

Fusible interfacing:
1. Back neck facing - cut 1
2. Front neck facing - cut 1

## Инструкции:

1. Apply fusible interfacing.

2. Sew darts on front, press bulk towards top.

3. Fold belts in half lengthwise right sides together and sew along long side and one short side. Belt turn right side out, straighten and press.

4. Serge the vertical edges on left and right fronts separately. Sew правую and левую полочки from top to the mark for the slit, inserting left belt, serge the seam allowances on the slanted area and press towards center. Press apart seam allowances on the vertical area. Topstitch sides of the slit at 0.1 cm from fold.

5. Sew shoulder and side seams, inserting the right belt into the right seam, press towards the back and serge.

6. Sew the shoulder seams of the neckline facings, press the seam apart. Serge the outer edge. Pin facing to garment right sides together and sew the neckline. Fold the facing onto wrong side, straighten, press. Secure the facing to the main garment along the shoulder seams.

7. Sew sleeve seam, press towards the back and serge. Sew sleeves into armholes, matching notches, serge and press.

8. Seam allowance for hem of garment and hem of sleeve serge, press onto wrong side and topstitch.

## Технический рисунок:

